

YANTON®
PROFESSIONAL FM TRANSCEIVER

Air band 118-135.975
MHz RX only;

Type-C charging port



T-360UV

Dual band, Dual display, dual standby

- Output power:5W
- 136-174MHz & 400-480MHz
- 2*128 channels
- Compander
- Noise canceling function (optional)
- Waterproof IP67(optional)
- Double PTT
- 2 Tone
- Scrambler

YANTON®
PROFESSIONAL FM TRANSCEIVER

T-360UV

Dual band, Dual display, dual standby
Air band 118-135.975MHz RX only;

- Output power:5W
- 136-174MHz & 400-480MHz
- 2*128 channels
- Waterproof IP67(optional)
- Noise canceling function (optional)
- Double PTT
- 2 Tone
- Scrambler
- Compander

Type-C charging port



General

Frequency Range	136-174MHz & 400-480MHz; Air band 118-135.975MHz RX only;
Antenna	High Gain Antenna
Frequency Stability	±2.5ppm
Memory Channel	2*250Channels
Working voltage	DC 7.4V
Antenna Impedance	50Ω
Operating Mode	simplex or co-frequency or alien
Dimensions	116*61*38mm
Battery Capacity	1500MaAH Li-in Battery

Packing list



TRANSMIT PART

RF power	5W
Modulate Mode	F3E
Max. Freq. Deviation	≤5KHz
Remain Wave Radiation	≤60db
Transmitting Current	≤1000mah

RECEIVER PART

Sensitivity	<0.20uV (12dB SINAD)
Squelch Sensitivity	<0.20uV
Intermodulation Antijamming	50db
Audio Power output	500mW
Receiving Current	≤100mh
Squelch Standby	20ma

QUANZHOU YANTON ELECTRONICS CO.,LTD

<http://www.yantonradio.com>